This Set

12-1

Material from Section 4.3

This set under construction.

Outline

- Branch Prediction Overview
- One-Level Predictor
- Two-Level Correlating Predictor
- Other topics to be added.
- Sample Problems

Branch and Target Prediction

12-2

Motivation

Branches occur frequently in code.

At best, one cycle of branch delay; more with dependencies.

Therefore, impact on CPI is large.

Techniques

- *Branch Prediction*
  Predict outcome of branch. (Taken or not taken.)
- *Branch Target Prediction*
  Predict branch or other CTI's target address.
- *Branch Folding*
  Replace branch or other CTI with target instruction.

Branch Prediction

12-3

Methods Covered

- *One-level predictor*
- (m, n) *two-level correlating predictor* or (m, n) *predictor* for short.

Branch Prediction Idea

12-4

Idea: Predict based on assumption that patterns hold.

Example:

```
LOOP:
 lw    r1, 0(r2)   ! Read random number, either 0 or 1.
 addi  r2, r2, #4
 slt   r6, r2, r7
 beqz  r1, SKIP
 addi  r3, r3, #1
SKIP:
 bneq  r6, LOOP    ! Loop executes 100 iterations.
 nop
```

Second branch, `bneq`, taken 99 out of 100 executions.

Pattern for `bneq`: T T T ... NT T T T

First branch shows no pattern.

EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.

12-4

12-5

Prediction Accuracy

SPEC89 benchmarks on IBM POWER (predecessor to PowerPC).



FIGURE 4.14 Prediction accuracy of a 4096-entry two-bit prediction buffer for the SPEC89 benchmarks.

12-5

12-6



FIGURE 4.15 Prediction accuracy of a 4096-entry two-bit prediction buffer versus an infinite buffer for the SPEC89 benchmarks.

EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.
12-6

12-7

Branch Prediction Terminology

Outcome [of a branch instruction execution].
The outcome of the execution of a branch instruction.

T
A taken branch.

NT or *N*
A branch that was not taken.

Prediction [made by branch prediction hardware].
The predicted outcome of a branch.

Misprediction
An incorrectly predicted outcome.

Prediction Accuracy [of a branch prediction scheme].
The number of correct predictions divided by the number of predictions.

EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.
12-7

Branch Prediction Terminology (Continued)

12-8

Speculative Execution

The execution of instructions following a predicted branch.

Misprediction Recovery

Undoing the effect of speculatively executed instructions . . .

. . . and re-starting instruction fetch at the correct address.

12-9

One-Level Branch Predictor

Idea: maintain a *branch history* for each branch instruction.

Branch histories stored in a *branch history table*.

Branch history can be an arbitrary finite state machine or a *counter*.

Branch outcome causes a change in branch history.

Branch prediction based on state of branch history.

12-10

Branch History Counter

If a counter used, branch history incremented when branch taken...
... and decremented when branch not taken.

Symbol n denotes number of bits for branch history.

To save space and for performance reasons ...
... branch history limited to a few bits, usually $n = 2$.

Branch history updated using a *saturating counter*.

A saturating counter is an arithmetic unit that can add or subtract one ...
... in which $x + 1 \rightarrow x + 1$ for $x \in [0, 2^n - 2]$ ...
... $x - 1 \rightarrow x - 1$ for $x \in [1, 2^n - 1]$ ...
... $(2^n - 1) + 1 \rightarrow 2^n - 1$ ...
... and $0 - 1 \rightarrow 0$.

For an n-bit counter, predict taken if counter $> 2^{n-1}$.

EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.

12-10

One-Level Branch Predictor Hardware

12-11

Illustrated for Chapter-3 DLX implementation . . .
. . . even though prediction not very useful.

Branch Prediction Steps

- Predict.
  Read branch history, available in ID.
- Determine Branch Outcome
  Execute predicted branch in usual way.
- Recover (If necessary.)
  Undo effect of speculatively executing instructions, start fetching from correct path.
- Update Branch History

Branch History Table

12-12

Branch History Table

Stores branch histories,

Implemented using a memory device.

Address (called index) is *hash* of branch address (`PC`).

For 2^m-entry BHT, hash is m lowest bits of branch PC **skipping alignment**.



Data input and output of BHT is branch history.

EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.

12-12

12-13

Sample Local History

Outcomes for individual branches, categorized by pattern, sorted by frequency.

Branches running TEX text formatter compiled for SPARC (Solaris).

```
Arbitrary, pat 60288, br732164, 0.7743 0.7170 0.7199  (0.19675)
          % Patterns # Branches gshre local  corr   Local History
  0:      fe7f  0.0004     1397  0.912 0.916 0.896  TTTTTTTNNTTTTTTT  0
  1:      ff3f  0.0004     1323  0.924 0.909 0.900  TTTTTTNNTTTTTTTT  0
  2:      fcff  0.0004     1317  0.949 0.939 0.948  TTTTTTTTNNTTTTTT  0
  3:      ff9f  0.0003     1245  0.910 0.905 0.898  TTTTTNNTTTTTTTTT  0
  4:      f9ff  0.0003     1235  0.955 0.950 0.955  TTTTTTTTTNNTTTTT  0
  5:      ffcf  0.0003     1188  0.926 0.921 0.923  TTTTNNTTTTTTTTTT  0
  6:        60  0.0003     1163  0.873 0.829 0.854  NNNNNTTNNNNNNNNN  0
  7:       180  0.0003     1159  0.955 0.914 0.926  NNNNNNNTTNNNNNNN  0
  8:       300  0.0003     1158  0.949 0.926 0.934  NNNNNNNNTTNNNNNN  0
  9:        c0  0.0003     1155  0.944 0.917 0.926  NNNNNNTTNNNNNNNN  0
```

12-14

Short Loop, pat 124, br 137681, 0.8908 0.9055 0.7441 (0.03700)

	% Patterns	# Branches	gshre	local	corr	Local History	
0:	5555	0.0040	14753	0.987	0.981	0.912	TNTNTNTNTNTNTNTN	1
1:	aaaa	0.0040	14730	0.859	0.978	0.461	NTNTNTNTNTNTNTNT	1
2:	9249	0.0022	8062	0.997	0.992	0.988	TNNTNNTNNTNNTNNT	1
3:	4924	0.0022	8055	0.997	0.998	0.998	NNTNNTNNTNNTNNTN	1
4:	2492	0.0022	8047	0.993	0.991	0.009	NTNNTNNTNNTNNTNN	1
5:	db6d	0.0013	4864	0.713	0.915	0.065	TNTTNTTNTTNTTNTT	1
6:	b6db	0.0013	4713	0.862	0.903	0.926	TTNTTNTTNTTNTTNT	1
7:	6db6	0.0012	4640	0.991	0.978	0.970	NTTNTTNTTNTTNTTN	1
8:	bbbb	0.0008	3061	0.896	0.936	0.949	TTNTTTNTTTNTTTNT	1

Long Loop?, pat 32, br 185795, 0.9170 0.9052 0.9096 (0.04993)

0:	fffe	0.0025	9204	0.902	0.930	0.913	NTTTTTTTTTTTTTTT	2
1:	8000	0.0025	9198	0.654	0.700	0.705	NNNNNNNNNNNNNNNT	2
2:	7fff	0.0022	8052	0.890	0.817	0.818	TTTTTTTTTTTTTTTN	2
3:	ffbf	0.0018	6800	0.933	0.908	0.920	TTTTTTNTTTTTTTTT	2
4:	feff	0.0018	6782	0.946	0.938	0.942	TTTTTTTTNTTTTTTT	2
5:	ff7f	0.0018	6778	0.949	0.946	0.950	TTTTTTTNTTTTTTTT	2
6:	fdff	0.0018	6738	0.947	0.941	0.946	TTTTTTTTTNTTTTTT	2
7:	1	0.0018	6690	0.955	0.945	0.942	TNNNNNNNNNNNNNNN	2
8:	fffd	0.0018	6667	0.968	0.966	0.967	TNTTTTTTTTTTTTTT	2

EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.
12-14

12-15

```
Phase Change, pat 26, br 48190, 0.8453 0.9040 0.8470  (0.01295)
          % Patterns # Branches gshre local  corr   Local History
  0:      c000  0.0012     4554  0.653 0.777 0.680  NNNNNNNNNNNNNNTT  3
  1:      e000  0.0009     3420  0.714 0.859 0.758  NNNNNNNNNNNNNTTT  3
  2:      f000  0.0008     2942  0.756 0.888 0.788  NNNNNNNNNNNNTTTT  3
  3:      fffc  0.0008     2878  0.908 0.960 0.959  NNTTTTTTTTTTTTTT  3
  4:      f800  0.0007     2642  0.786 0.917 0.827  NNNNNNNNNNNTTTTT  3
  5:         3  0.0007     2572  0.968 0.952 0.951  TTNNNNNNNNNNNNNN  3
  6:      fc00  0.0007     2435  0.815 0.933 0.854  NNNNNNNNNNTTTTTT  3
  7:      fe00  0.0006     2225  0.836 0.936 0.876  NNNNNNNNNTTTTTTT  3
  8:      ff00  0.0006     2140  0.856 0.947 0.931  NNNNNNNNTTTTTTTT  3
  9:      ff80  0.0006     2061  0.854 0.941 0.934  NNNNNNNTTTTTTTTT  3


One Way, pat    2, br  2617433, 0.9917 0.9934 0.9897  (0.70337)
  0:      ffff  0.5151  1916950  0.993 0.996 0.993  TTTTTTTTTTTTTTTT  4
  1:         0  0.1882   700483  0.988 0.986 0.982  NNNNNNNNNNNNNNNN  4
```


EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.
12-15

Steps in BHT Use (refers to example.)

12-16

Register `r1` not available until cycle ten[1].

When branch in ID, read BHT and make prediction. (Cycle 1)

(Optional) Backup (checkpoint) register map (if present).

Execute branch in usual way and check prediction. (Cycle 10.)

If prediction correct, update BHT when branch commits (Cycle 11.).

If prediction wrong, start recovery process (does not occur here).

```
! Predict not taken, not taken.
Cycle:             0   1   2    3              10   11   12  13
 bneq r1, TARGET  IF  ID  0:RS 0:RS ...       0:B  0:WC
 xor r2, r3, r4       IF    ID 5:EX 5:WB              5:C
                                                        6:C
 ...
TARGET:
 and r5, r6, r7
```

[1] Perhaps due to a cache miss, or maybe it depended on a long-latency floating-point operation, the reason is not important

12-17

BHT use when branch taken, correctly predicted.

Register `r1` not available until cycle 10.

When branch in ID, compute target, read BHT and make prediction. (Cycle 1).

Execute branch in usual way and check prediction. (Cycle 10.)

Commit branch after `div`. (Cycle 23).

```
! Predict taken, taken.
Cycle:            0   1   2    3              10   11   ... 21  22 23
 div f0,f2, f4    ID  DIV                                   DIV WC
 bneq r1, TARGET  IF  ID  0:RS 0:RS ...       0:B  0:WB           C
 xor r2, r3, r4       IFx

 ...
TARGET:
 and r5, r6, r7           IF...                                    C
```


EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.
12-17

12-18

BHT use when branch taken, incorrectly predicted, register map *not* backed up.

Register `r1` not available until cycle 10.

When branch in ID, compute target, read BHT and make prediction. (Cycle 1).

Cycle 10: ooops, misprediction. Because register map not backed up, recovery must wait until commit.

Cycle 23: Start recovery: Squash instructions in reorder buffer, start fetching correct path.

```
! Predict not taken, taken. Register map not backed up.
Cycle:            0   1   2    3              10   11   ... 21  22 23
 div f0,f2, f4    ID  DIV                                   DIV WC
 bneq r1, TARGET  IF  ID  0:RS 0:RS ...       0:B  0:WB          C
 xor r2, r3, r4       IF    ID   EX ...

 ...
TARGET:
 and r5, r6, r7                                                IF ....
```


EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.
12-18

12-19

BHT use when branch taken, incorrectly predicted, register map backed up.

Register `r1` not available until cycle 10.

When branch in ID, backup (checkpoint) register map, compute target, read BHT and make prediction. (Cycle 1).

Cycle 10: ooops, misprediction. Squash reorder buffer past branch, switch to backed up register map, start fetching correct path.

Cycle 23: Branch commits.

```
! Predict not taken, taken. Register map backed up.
Cycle:            0   1   2    3              10   11   ... 21  22 23
 div f0,f2, f4    ID  DIV                                   DIV WC
 bneq r1, TARGET  IF  ID  0:RS 0:RS ...       0:B  0:WB           C
 xor r2, r3, r4       IF    ID   EX

 ...
TARGET:
 and r5, r6, r7                                    IF ....
```


EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.
12-19

12-20

(m, n) Two-Level Correlating Predictor

Idea: Base branch decision on ...

... the identity of the branch instruction (as in the one-level scheme) ...

... and the most recent branch outcomes (global history).

Global History

The outcome of the most recent branches.

In an (m, n) predictor, interested in m most-recent branches.

Global History Example

12-21

```
! Loop always iterates 4 times.
! Branch below never taken.
 bneq r2, SKIP      N                       N
 addd f0, f0, f2
SKIP:
 addi  r1, r0, #4
LOOP:
 multd f0, f0, f2
 subi  r1, r1, #1
 bneq  r1, LOOP          T   T   T   N    ... T   T   T   N  ...
! Cycle               10  20  30  40  50  110 120 130 140 150
!
! Global History (m=4), X: depends on earlier branches.
! 10  XXXN  Human would predict taken.
! 20  XXNT  Human would predict taken.
! 30  XNTT  Human would predict taken.
! 40  NTTT  Human would predict not taken.
! 50  TTTN
```

12-22

BHT Indexing for (m, n) Predictor

Two methods of generating address for BHT:

gselect: Concatenate global history with branch address.

gshare: Exclusive-or global history with branch address.

gselect is easier to understand, but gshare uses BHT more efficiently.

Global History and Dynamic Scheduling

12-23

Global history must be accurate.

Why that's a problem:

```
! First branch: Predict not taken, taken.  Register map backed up.
Cycle:            0   1   2    3              10   11     12   13 ... 21  22 23
 div f0,f2, f4    ID  DIV                                            DIV WC
 bneq r1, TARGET  IF  ID  0:RS 0:RS ...       0:B  0:WB                    C
 beqz r2, SKIP        IF    ID 1:B  ...
 xor r2, r3, r4             IF   ID   EX ...


 ...
TARGET:
 and r5, r6, r7                                   IF   ID   EX ...
 beqz r4, LINE1                                        IF   ID ...
Cycle:            0   1   2    3              10   11     12   13 ... 21  22 23
```

Cycle 2: `beqz` should see global history with `bneq` not taken.

Global history includes *assumption* that `bneq` not taken.

EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.

12-23

12-24

```
! First branch: Predict not taken, taken.  Register map backed up.
Cycle:             0   1   2    3              10   11     12   13 ... 21  22 23
 div f0,f2, f4     ID  DIV                                            DIV WC
 bneq r1, TARGET   IF  ID  0:RS 0:RS ...       0:B  0:WB                    C
 beqz r2, SKIP         IF    ID 1:B  ...
 xor r2, r3, r4              IF   ID   EX ...

 ...
TARGET:
 and r5, r6, r7                                    IF   ID   EX ...
 beqz r4, LINE1                                         IF   ID ...
Cycle:             0   1   2    3              10   11     12   13 ... 21  22 23
```

Cycle 3: Now global history includes assumption that `bneq` and first `beqz` not taken.

Cycle 11: Ooops, `bneq` misprediction discovered.

Global history has two incorrect assumptions ...
... unless they're fixed prediction for second `beqz` won't be accurate.

Cycle 12: `beqz` should see global history with `bneq` taken.

Global History and Dynamic Execution

12-25

Global History in Two-Level Predictor with Dynamic Execution

Global history backed up (*checkpointed*) at each branch.

Predicted outcome shifted in to global history.

If misprediction discovered, global history restored from backup ...
... just as the register map can be.

Target Prediction and Folding

12-26

Target Prediction

Predicting the outcome and target of a branch.

Branch Target Buffer

A table indexed by branch address holding a predicted target address.

Target Prediction

Put BTB in IF stage.

Use PC to read an entry from BTB.

If valid entry found, replace PC with predicted target.

With target correctly predicted, zero branch delay.

12-27

Target Prediction Example

Static scheduled system (for clarity).

```
Cycle:              0   1   2   3   4              10  11  12  13  14
 bneq r1, TARGET    IF  ID  EX  MEM WB             IF  ID  EX  MEM WB
 xor  r2, r3, r4                                       IF  ID  EX

TARGET:
 and  r5, r6, r7        IF  ID  EX  MEM WB            IF  X
```

Cycle 0

BTB lookup and prediction. Predict taken.

Target from BTB will be clocked into `PC`.

12-27

12-28

Target Prediction Example, continued.

Static scheduled system (for clarity).

```
Cycle:              0   1   2   3   4              10  11  12  13  14
 bneq r1, TARGET    IF  ID  EX  MEM WB             IF  ID  EX  MEM WB
 xor  r2, r3, r4                                       IF  ID  EX

TARGET:
 and  r5, r6, r7        IF  ID  EX  MEM WB            IF  X
```

Cycle 1

Start fetching predicted target.

Execute branch instruction (in `ID`).

Check predicted outcome and predicted target.

Correct predictions, continue execution.

Target Prediction Example, continued.

12-29

```
Cycle:              0   1   2   3   4              10  11  12  13  14
 bneq r1, TARGET    IF  ID  EX  MEM WB             IF  ID  EX  MEM WB
 xor  r2, r3, r4                                        IF  ID  EX

TARGET:
 and  r5, r6, r7        IF  ID  EX  MEM WB             IF  X
```

Cycle 10

BTB lookup and prediction. Predict taken.

Target from BTB will be clocked into `PC`.

Cycle 11

Start fetching predicted target.

Execute branch instruction (in `ID`).

Ooops, incorrect outcome prediction ...
... replace target with `nop` ...
... and clock correct target into `PC`.

EE 4720 Lecture Transparency. Formatted 13:31, 2 December 1999 from lsli12.

12-29

Target Prediction for Register-Indirect CTI

12-30

What is being predicted:

That instruction will be a CTI.

If CTI is a branch, that branch is taken.

CTI target.

For branches and non-indirect jumps (`j`, `jal`)...
... predicting target is easy, since target always same.

For register-indirect jumps (`jr`, `jalr`) ...
... prediction depends on predictable behavior.

Target Prediction

12-31

Two Methods

Predict last target.

Keep a stack of (what appear to be) return addresses.

For most CTIs . . .
. . . use last target as prediction for next target.

Assuming a BTB hit . . .
. . . last target works perfectly for non-indirect CTIs . . .
. . . but depends on register value not changing for indirect CTIs.

If call and return instructions can be perfectly identified . . .
. . . call stack will make perfect prediction for return instructions.

Target Prediction Example

12-32

Consider code for C `switch` statement:

```
! Possible code for a switch statement.
! switch( r2 ) { case 0: foo(); break; case 1: bar(); break; ... }
! Set r1 to base of switch address table.
 lhi  r1, #0x1234
 ori  r1, r1, #0x5670
! Multiply switch index by stride of table (4 bytes per address).
 slli r3, r2, #2
! Get address of case code address.
 add  r1, r1, r3
! Get case code address.
 lw   r4, 0(r1)
! Jump to case code.
 jr   r4
```

If `r2` rarely changes, `jr` predictable.

BTB Contents

12-33

Possible BTB Contents

Target address.

History information (instead of in BHT).

Tag, to detect collisions.